

Cab Seat Belt Control

Submitted by August 2006
Richard Cox (r.w.cox@ieee.org),
Holly Towne (towne@oneweaver.com), Ray Wilkes (raydad@prodigy.net)

Wrangle, rope and tie those stray cab seat belts.
Here are three ways to tame those seat belts.

Originated Harry Pinchot, submitted by Richard Cox



APPROX. MODIFICATION TIME 10 min.

PARTS LIST

All prices are approximate and pre-tax.

| | |
|------------------------------------|--------------|
| Two mini-bungee cords, 12" | < \$1 each |
| APPROX. TOTAL COST OF PARTS | ~ \$2 |

INSTRUCTIONS

Installing the bungee cords is best accomplished by kneeling on the front seat while facing the seat back. Position a knee on the seat cushion close to the seat back and depress the cushion as much as possible. Reach in with one hand between the cushion and the back and locate a metal rod running horizontally across the width of the seat. You will want to get to the rod close to the edge of the seat. On the driver's seat, this will be on the left as you are facing the seat, and it will be on the right for the passenger seat. Hook one end of the bungee cord over the rod and bring the other end out towards the edge of the seat. (NOTE: On some drivers seats there may be a rod for a lumbar adjustment; do not hook the cord to this rod.) Wrap the cord around the seat belt cable just below the buckle and secure with the hook on the other end of cord. Unhook and unwrap the cord to turn the seat.

From the Rialta Yahoo site, submitted by Holly Towne



APPROX. MODIFICATION TIME 10 min.

PARTS LIST

All prices are approximate and pre-tax.

| | |
|------------------------------------|--------------|
| Two mini-bungee cords, 12" | < \$1 each |
| Two carabiner clips | \$2 each |
| APPROX. TOTAL COST OF PARTS | ~ \$6 |

INSTRUCTIONS

Hook both ends of the bungee cord around the bar in the seat, as described in the above version of this modification. Attach a carabiner clip to the loop and snap it over the stem of the seat belt anchor. Release the clip whenever you want to turn the cab seat.

Originated El Hargis, submitted by Ray Wilkes



APPROX. MODIFICATION TIME 2 min.

PARTS LIST

All prices are approximate and pre-tax.

| | |
|--|------------|
| Two bungee cords 6" to 10" with the two ends of the bungee cords are linked together by a plastic ball | < \$1 each |
| APPROX. TOTAL COST OF PARTS | ~ \$2 |

INSTRUCTIONS

Since we want to turn the right seat each night, all we do is loop the ball bungee around the seat belt anchor, and back through itself. Then just push the ball part of the bungee down in between the back of the seat and the seat itself. This way, to turn the seat, just remove the ball from the seat crack and turn the chair.

Updated
Saturday, 30 September, 2006

© All photos, intellectual property, and modifications herein are copyright by a TechRally group member. 2006 ©