



X-X FOR DRAINAGE CALLOUTS SEE DWG NO. 116229-01-000

222 RD US/CANADIAN

- (265) CODES/STANDARDS-CSA/CMVSS
- (1B1) CODES STANDARDS/USA
- (1A7) SHOWER PACKAGE-WITHOUT
- (140) SHOWER PACKAGE

5. EXPOSED PIPE ABOVE ROOF TO BE PAINTED 37163-01-000.
4. ALL EXTERIOR OPENINGS AROUND PIPE TO BE SEALED WITH 69637-01-000.
3. ALL PIPE AND FITTINGS TO BE ASSEMBLED WITH SOLVENT 4020-01-000.
2. SLOPE OF TRAP ARM MUST BE 6 PER 305.
1. SLOPE OF HORIZONTAL PIPING TO BE 6 PER 305 MIN.
- (9) USE SCRAP CLOSED CELL NEOPRENE FROM 77075-01.-02 OR -03 ON HAT CHANNELS FOR VIBRATION DAMPENING.
- (8) VENT PIPE MUST PROJECT 51 MIN AND 63.5 MAX ABOVE ROOF FOR PROPER FIT AND FUNCTION.
- (7) SEE DWG 61607-01-000 FOR INSTALLATION OF GROMMET.
6. FOR CAN UNITS EACH HOLDING TANK SHALL HAVE A CSA APPROVAL STAMPED NEAR THE IAMPO APPROVAL.
10. SECURE PIPES TO CABINET USING WIRE TIE 108046-02-000 AND SCREW G67-10-12U (8).

LAYOUT NO. 200GEN		TITLE: DRAINAGE SYSTEM INSTL	
DATE	DATE	UNDESIGNED TOLERANCES ARE:	MATERIAL:
DATE	DATE	WHOLE DIM (IN) ± .5	
DATE	DATE	ONE-PLACE (IN) ± .1	
DATE	DATE	TWO-PLACE (IN) ± .01	
DATE	DATE	THREE-PLACE (IN) ± .005	
DATE	DATE	FOUR-PLACE (IN) ± .002	
DATE	DATE	FIVE-PLACE (IN) ± .001	
DATE	DATE	SIX-PLACE (IN) ± .0005	
DATE	DATE	SEVEN-PLACE (IN) ± .0002	
DATE	DATE	EIGHT-PLACE (IN) ± .0001	
DATE	DATE	NINE-PLACE (IN) ± .00005	
DATE	DATE	TEN-PLACE (IN) ± .00002	
DATE	DATE	ELEVEN-PLACE (IN) ± .00001	
DATE	DATE	UNDESIGNED TOLERANCES ARE:	
DATE	DATE	WHOLE DIM (IN) ± .5	
DATE	DATE	ONE-PLACE (IN) ± .1	
DATE	DATE	TWO-PLACE (IN) ± .01	
DATE	DATE	THREE-PLACE (IN) ± .005	
DATE	DATE	FOUR-PLACE (IN) ± .002	
DATE	DATE	FIVE-PLACE (IN) ± .001	
DATE	DATE	SIX-PLACE (IN) ± .0005	
DATE	DATE	SEVEN-PLACE (IN) ± .0002	
DATE	DATE	EIGHT-PLACE (IN) ± .0001	
DATE	DATE	NINE-PLACE (IN) ± .00005	
DATE	DATE	TEN-PLACE (IN) ± .00002	
DATE	DATE	ELEVEN-PLACE (IN) ± .00001	

